Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 112

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 140mm ean 10904

Material: Solid Rubber tyre Core: Steel Application field: Industry

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN5:10904 Article code:01080BF1400CN EAN13:8018793109048



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 115 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 80

Stoneware

Flooring

Asphalt

Concrete

Wheel data

Diameter (mm)	140
Band width (mm)	38
Hub width (mm)	43
Hub version	Ball bearing
Wheel hole (mm)	10
Bearing seat (mm)	1
Dynamic load capacity (DaN)	115
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	I
Offset (mm)	45
Ground clearance (mm)	173
Castor hole (mm)	1
Static load capacity (DaN)	150
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized