Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 112

103

 $\ensuremath{\mathsf{AVO}}$ - Wheel with solid rubber tyre and steel castor for industry, diameter 140mm ean 18316

Material: Solid Rubber tyre Core: Steel Application field: Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:8018793183161 **EAN5**:18316 **Article code**:03103001400RN



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 115 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 80

Flooring

- Asphalt
- ConcreteStoneware

Wheel data

Diameter (mm)	140
Band width (mm)	38
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	115
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	45
Ground clearance (mm)	176
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	1
Stem type	/
Finishing	Galvanized