

SERIE 112AM

# 103B-AM

**AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 150mm**

**Material:** Solid Rubber tyre    **Core:** Steel    **Scope:** Industry

**Description:**

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:/    EAN5:/    Article code:**03103B01500RG



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 135 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore A    **Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	135
Colour	Grey
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	/
Static load capacity (DaN)	170
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized