Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 112AM

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 150mm

Application field: Industry Material: Solid Rubber tyre Core: Steel

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Rubber tyre

EAN13:/ EAN5:/ Article code:03103B01500RG



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 135 DaN

Hardness: 80 Rotation: Roller bearing Hardness scale: Shore A

Concrete Stoneware

Flooring

Asphalt

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	135
Colour	Grey
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
riate size (iiiii)	,
Plate hole spacing (mm)	/
Plate hole size (mm)	1
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	/
Static load capacity (DaN)	170
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized