Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 112

80BISBI

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 150mm ean 04008

Material: Solid Rubber tyre Core: Steel Application field: Industry

Description

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793040082 **EAN5**:04008 **Article code**:01080BFI150RN



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 135 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 80

Flooring

- Asphalt
- ConcreteStoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	1
Dynamic load capacity (DaN)	135
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

But to the total	,
Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	1
Static load capacity (DaN)	170
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	40X90
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized