

SERIE 112

## 80BIS

**AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 150mm ean 04232**

**Material:** Solid Rubber tyre    **Core:** Steel    **Application field:** Industry

**Description:**

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:**8018793042321    **EAN5:**04232    **Article code:**01080F01501BN



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 135 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore A    **Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                   |
|-----------------------------|-------------------|
| Diameter (mm)               | 150               |
| Band width (mm)             | 40                |
| Hub width (mm)              | 50                |
| Hub version                 | Plain bore        |
| Wheel hole (mm)             | 15                |
| Bearing seat (mm)           | /                 |
| Dynamic load capacity (DaN) | 135               |
| Colour                      | Black             |
| Material                    | Solid Rubber tyre |
| Box pieces                  | /                 |
| Hardness scale              | Shore A           |
| Hardness                    | 80                |

## Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 140X110          |
| Plate hole spacing (mm)    | 105X080          |
| Plate hole size (mm)       | 11X16            |
| Offset (mm)                | 45               |
| Ground clearance (mm)      | 181              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 170              |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Rear             |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Galvanized       |