

SERIE 112

80BISB

AVO - Wheel with solid rubber tyre and steel castor for industry,
diameter 150mm ean 10905

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793109055 **EAN5:**10905 **Article code:**01080BF1500CN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 135 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------------|
| Diameter (mm) | 150 |
| Band width (mm) | 40 |
| Hub width (mm) | 43 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 10 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 135 |
| Colour | Black |
| Material | Solid Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 45 |
| Ground clearance (mm) | 178 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 170 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Rear |
| Plain axle | 22X50 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |