

SERIE 112A

103B

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 150mm ean 13078

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Solid rubber wheel 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on roller bearings, shielded ball bearings or plain bore. /

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793130783 **EAN5:**13078 **Article code:**03103SB1500CN

Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 135 DaN

- Asphalt
- Concrete
- Stoneware

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	43
Hub version	Ball bearing
Wheel hole (mm)	10
Bearing seat (mm)	/
Dynamic load capacity (DaN)	135
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	45
Ground clearance (mm)	178
Castor hole (mm)	/
Static load capacity (DaN)	170
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized