

SERIE 112B

## 90ANTB

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 160mm ean 11117

**Material:** Solid Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793111171 **EAN5:**11117 **Article code:**02090BA1600RN



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 140 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 83

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	140
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	/
Static load capacity (DaN)	180
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized