Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 112

# 103B

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 160mm ean 15575

Material: Solid Rubber tyre Core: Steel Application field: Industry

#### Description

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

#### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

**EAN13**:8018793155755 **EAN5**:15575 **Article code**:03103BI160SBN



### **Features**

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 150 DaN

Rotation: Plain bore Hardness scale: Shore A Hardness: 80

# **Flooring**

- AsphaltConcrete
- Stoneware

#### Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	150
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	1
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	35X120
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized