Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 112

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 160mm ean 15655

Material: Solid Rubber tyre Core: Steel Application field: Industry

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN5:15655 Article code:01080BFS160RN EAN13:8018793156554



## **Features**

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 150 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 80

# **Flooring**

- Asphalt
- Concrete Stoneware

## Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	150
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	1
	,
Plate hole size (mm)	1
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	1
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	36X100
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized