

SERIE 112B

90BISB

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 180mm ean 04485

Material: Solid Rubber tyre

Core: Polypropylene

Application field: Industry

Description:

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793044851 **EAN5:**04485 **Article code:**02090FB1800RN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------------|
| Diameter (mm) | 180 |
| Band width (mm) | 45 |
| Hub width (mm) | 58 |
| Hub version | Roller bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 170 |
| Colour | Black |
| Material | Solid Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 83 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 55 |
| Ground clearance (mm) | 222 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 220 |
| Structure | Swivel |
| Version | Axle with brake |
| Brake | Rear |
| Plain axle | 22X50 |
| Stem type | Plain axle Stem(on request threaded stem) |
| Finishing | Galvanized |