

SERIE 112B

90BIS

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 180mm ean 04521

Material: Solid Rubber tyre

Core: Polypropylene

Application field: Industry

Description:

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:8018793045216

EAN5:04521

Article code:02090F01800RN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	45
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	225
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate with brake
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized