

SERIE 112

80F

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 180mm ean 11105

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793111058 **EAN5:**11105 **Article code:**010800F1800CN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 170 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------------|
| Diameter (mm) | 180 |
| Band width (mm) | 50 |
| Hub width (mm) | 55 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 17 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 170 |
| Colour | Black |
| Material | Solid Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| | |
|----------------------------|------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 55 |
| Ground clearance (mm) | 222 |
| Castor hole (mm) | 16 |
| Static load capacity (DaN) | 220 |
| Structure | Swivel |
| Version | Bolt hole |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |