

SERIE 112B

90ANTB

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 180mm ean 11118

Material: Solid Rubber tyre

Core: Polypropylene

Application field: Industry

Description:

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13: 8018793111188

EAN5: 11118

Article code: 02090BA1800BN



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 170 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	45
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	222
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized