

SERIE 112

103BI

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 180mm ean 14112

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793141123 **EAN5:**14112 **Article code:**03103BI1800RN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 170 DaN
Rotation: Roller bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	222
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	40X90
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized