Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 112

# 103B

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 180mm ean 15633

Material: Solid Rubber tyre Core: Steel Application field: Industry

#### Description

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

#### Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

**EAN13**:8018793156332 **EAN5**:15633 **Article code**:03103BI180IBN



#### **Features**

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 170 DaN

Rotation: Plain bore Hardness scale: Shore A Hardness: 80

### Asphalt

**Flooring** 

- ConcreteStoneware

#### Wheel data

| Diameter (mm)               | 180               |
|-----------------------------|-------------------|
| Band width (mm)             | 50                |
| Hub width (mm)              | 58                |
| Hub version                 | Plain bore        |
| Wheel hole (mm)             | 20                |
| Bearing seat (mm)           | 1                 |
| Dynamic load capacity (DaN) | 170               |
| Colour                      | Black             |
| Material                    | Solid Rubber tyre |
| Box pieces                  | 1                 |
| Hardness scale              | Shore A           |
| Hardness                    | 80                |

## Support data

| Plate size (mm)            | 1   |
|----------------------------|---|
| Plate hole spacing (mm)    | 1   |
| Plate hole size (mm)       | 1   |
| Offset (mm)                | 55  |
| Ground clearance (mm)      | 222                                       |
| Castor hole (mm)           | 1   |
| Static load capacity (DaN) | 220                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle with brake                           |
| Brake                      | Front                                     |
| Plain axle                 | 40X190                                    |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |