

SERIE 112

## 80BI

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 200mm ean 15588

**Material:** Solid Rubber tyre    **Core:** Steel    **Application field:** Industry

**Description:**

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

in zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793155885    **EAN5:**15588    **Article code:**01080BI200ZRN



### Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 205 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore A    **Hardness:** 80

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	205
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	232
Castor hole (mm)	/
Static load capacity (DaN)	260
Structure	Swivel
Version	Axle
Brake	/
Plain axle	35X120
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized