

SERIE 112

80BISBI

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 200mm ean 15660

Material: Solid Rubber tyre **Core:** Steel **Scope:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793156608 **EAN5:**15660 **Article code:**01080BFS200RN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 205 DaN
Rotation: Roller bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	205
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	232
Castor hole (mm)	/
Static load capacity (DaN)	260
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	36X100
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized