

SERIE 112

80BI

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 225mm ean 04094

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

in zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut.

Product line: Rubber tyre

EAN13:8018793040945 **EAN5:**04094 **Article code:**01080BI2250CN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 250 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	225
Band width (mm)	55
Hub width (mm)	55
Hub version	Ball bearing
Wheel hole (mm)	17
Bearing seat (mm)	/
Dynamic load capacity (DaN)	250
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	252
Castor hole (mm)	/
Static load capacity (DaN)	320
Structure	Swivel
Version	Axle
Brake	/
Plain axle	40X90
Stem type	Stem(on request threaded stem) Plain axle
Finishing	Galvanized