

SERIE 112

80B

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 250mm ean 04181

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793041812 **EAN5:**04181 **Article code:**01080B02500CN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 300 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	64
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	85
Ground clearance (mm)	298
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle
Brake	/
Plain axle	25X55
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized