Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 112

80BISB

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 250mm ean 11537

Material: Solid Rubber tyre Core: Steel Application field: Industry

Description

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793115377 **EAN5**:11537 **Article code**:01080BF2500CN



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 300 DaN

Rotation: Ball bearing Hardness scale: Shore A Hardness: 80

Flooring

- Asphalt
- ConcreteStoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	63
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	1
Dynamic load capacity (DaN)	300
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	85
Ground clearance (mm)	298
Castor hole (mm)	1
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X55
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized