

SERIE 604

605A

AVO - Wheel with solid rubber tyre and steel castor for industry,
diameter 250mm ean 27008

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Extra robust and solid elastic rubber wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Rubber tyre, Pneumatic

EAN13:8018793270083 **EAN5:**27008 **Article code:**21605A0250084



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 1350 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	84
Hub width (mm)	75
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	1350
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

Support data

Plate size (mm)	175X140
Plate hole spacing (mm)	140X105
Plate hole size (mm)	15
Offset (mm)	/
Ground clearance (mm)	305
Castor hole (mm)	/
Static load capacity (DaN)	1700
Structure	Fixed
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted