

SERIE 604

606

AVO - Wheel with solid rubber tyre and steel castor for industry,
diameter 306mm ean 23995

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Extra robust and solid elastic rubber wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, turning on thrust and tapered roller bearings, with plate. Black epoxy paint.

Product line: Rubber tyre, Pneumatic

EAN13:8018793239950 **EAN5:**23995 **Article code:**2160600306093



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 550 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	306
Band width (mm)	93
Hub width (mm)	75
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	550
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

Support data

Plate size (mm)	200X200
Plate hole spacing (mm)	160X160
Plate hole size (mm)	17
Offset (mm)	85
Ground clearance (mm)	375
Castor hole (mm)	/
Static load capacity (DaN)	690
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted