

SERIE 604

606A

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 306mm ean 24016

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Extra robust and solid elastic rubber wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Extra Heavy-Duty Castors:

Made of in pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Rubber tyre, Pneumatic

EAN13:8018793240161 **EAN5:**24016 **Article code:**21606A0306093



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 550 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

| | |
|-----------------------------|-------------------|
| Diameter (mm) | 306 |
| Band width (mm) | 93 |
| Hub width (mm) | 75 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 20 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 550 |
| Colour | Black |
| Material | Solid Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 70 |

Support data

| | |
|----------------------------|---------------|
| Plate size (mm) | 200X200 |
| Plate hole spacing (mm) | 160X160 |
| Plate hole size (mm) | 17 |
| Offset (mm) | / |
| Ground clearance (mm) | 375 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 690 |
| Structure | Fixed |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | Black painted |