

SERIE 604

# 607A

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 406mm ean 25139

**Material:** Solid Rubber tyre    **Core:** Steel    **Application field:** Industry

**Description:**

Extra robust and solid elastic rubber wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

**Twin Wheel Extra Heavy-Duty Castors:**

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

**Product line:** Rubber tyre, Pneumatic

**EAN13:**8018793251396    **EAN5:**25139    **Article code:**21607A0406104



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 1900 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 70

## Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

## Wheel data

|                             |                   |
|-----------------------------|-------------------|
| Diameter (mm)               | 406               |
| Band width (mm)             | 104               |
| Hub width (mm)              | 100               |
| Hub version                 | Ball bearing      |
| Wheel hole (mm)             | 25                |
| Bearing seat (mm)           | /                 |
| Dynamic load capacity (DaN) | 1900              |
| Colour                      | Black             |
| Material                    | Solid Rubber tyre |
| Box pieces                  | /                 |
| Hardness scale              | Shore A           |
| Hardness                    | 70                |

## Support data

|                            |               |
|----------------------------|---------------|
| Plate size (mm)            | 315X315       |
| Plate hole spacing (mm)    | 250X250       |
| Plate hole size (mm)       | 21            |
| Offset (mm)                | 100           |
| Ground clearance (mm)      | 535           |
| Castor hole (mm)           | /             |
| Static load capacity (DaN) | 2300          |
| Structure                  | Fixed         |
| Version                    | /             |
| Brake                      | /             |
| Plain axle                 | /             |
| Stem type                  | /             |
| Finishing                  | Black painted |