

SERIE 604

605A

AVO - Wheel with solid rubber tyre and steel castor for industry,
diameter 457mm ean 24313

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Extra robust and solid elastic rubber wheel 65-70 Shore A with zinc-chromium plated pressed steel flanges. Highly shock and cut resistant, high smoothness and vibration absorbing. Hub on shielded 2RS ball bearings or 2RS stainless steel ball bearings.

Twin Wheel Extra Heavy-Duty Castors:

Made of pressed and welded high thickness steel, fixed. Black epoxy paint.

Product line: Rubber tyre, Pneumatic

EAN13:8018793243131 **EAN5:**24313 **Article code:**21605A0457122



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 4200 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 70

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	457
Band width (mm)	122
Hub width (mm)	100
Hub version	Ball bearing
Wheel hole (mm)	25
Bearing seat (mm)	/
Dynamic load capacity (DaN)	4200
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	70

Support data

Plate size (mm)	315X315
Plate hole spacing (mm)	250X250
Plate hole size (mm)	21
Offset (mm)	100
Ground clearance (mm)	560
Castor hole (mm)	/
Static load capacity (DaN)	5250
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Black painted