

SERIE 112AM

103-AM

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 80mm

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:/ **EAN5:/** **Article code:**03103000800BG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 50 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	108
Castor hole (mm)	/
Static load capacity (DaN)	70
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized