

SERIE 112AM

103-AM

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 80mm

Material: Solid Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:/ EAN5:/ Article code:03103000800CG



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 50 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|------------------------------------|-------------------|
| Diameter (mm) | 80 |
| Band width (mm) | 25 |
| Hub width (mm) | 37 |
| Hub version | Ball bearing |
| Wheel hole (mm) | 8 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 50 |
| Colour | Grey |
| Material | Solid Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| | |
|-----------------------------------|------------------|
| Plate size (mm) | 100X085 |
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | 37 |
| Ground clearance (mm) | 108 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 70 |
| Structure | Swivel |
| Version | Plate with brake |
| Brake | Front |
| Plain axle | / |
| Stem type | / |
| Finishing | Galvanized |