Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



SERIE 112

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 80mm

Material: Solid Rubber tyre Core: Steel Application field: Industry

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:/ EAN5:/ Article code:03103B00804BN



Features

Minimum temperature: -20 Maximum temperature: 80 Dynamic load capacity: 50 DaN

Rotation: Plain bore Hardness scale: Shore A Hardness: 80

Flooring

- Asphalt
- Concrete Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	50
Colour	Black
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	1
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	10X30
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized