

SERIE 112

# 103

**AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 80mm ean 05151**

**Material:** Solid Rubber tyre    **Core:** Steel    **Application field:** Industry

**Description:**

Wheel with rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:**8018793051514    **EAN5:**05151    **Article code:**03103000800BN



## Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 50 DaN  
**Rotation:** Plain bore    **Hardness scale:** Shore A    **Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

<b>Diameter (mm)</b>	80
<b>Band width (mm)</b>	25
<b>Hub width (mm)</b>	40
<b>Hub version</b>	Plain bore
<b>Wheel hole (mm)</b>	12
<b>Bearing seat (mm)</b>	/
<b>Dynamic load capacity (DaN)</b>	50
<b>Colour</b>	Black
<b>Material</b>	Solid Rubber tyre
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	80

## Support data

<b>Plate size (mm)</b>	100X085
<b>Plate hole spacing (mm)</b>	080X060
<b>Plate hole size (mm)</b>	8,5X12
<b>Offset (mm)</b>	37
<b>Ground clearance (mm)</b>	108
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	70
<b>Structure</b>	Swivel
<b>Version</b>	Plate with brake
<b>Brake</b>	Front
<b>Plain axle</b>	/
<b>Stem type</b>	/
<b>Finishing</b>	Galvanized