Via XX Settembre, 107 28883 Gravellona Toce (VB) - Italia



SERIE 112CD

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 80mm ean 19287

Material: Solid Rubber tyre Core: Steel Application field: Industry

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Antistatic/Conductive

EAN13:8018793192873 EAN5:19287 Article code:03103B00802RA



Features

Minimum temperature: -25 Maximum temperature: 85 Dynamic load capacity: 50 DaN

Rotation: Roller bearing Hardness scale: Shore A Hardness: 80

Flooring

- Asphalt Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Solid Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	1
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	12X30
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized