

SERIE 112CD

# 103B-CD

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 80mm ean 20420

**Material:** Solid Rubber tyre    **Core:** Steel    **Application field:** Industry

**Description:**

Wheel with conductive rubber tyre 80 Shore A and zinc-chromium pressed steel flangers. Hub on roller bearings, shielded ball bearings or self-oiling bush.

**Medium duty castors:**

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

**Product line:** Antistatic/Conductive

**EAN13:**8018793204200    **EAN5:**20420    **Article code:**03103B00804RA



## Features

**Minimum temperature:** -25    **Maximum temperature:** 85    **Dynamic load capacity:** 50 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore A    **Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	80
Band width (mm)	25
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	10X30
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized