

SERIE 112B

## 90ANTB

AVO - Wheel with solid rubber tyre and steel castor for industry, diameter 80mm ean 21002

**Material:** Solid Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with Black rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793210027 **EAN5:**21002 **Article code:**02090BA0806BN



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 50 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 83

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Black
Material	Solid Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	/
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized