

SERIE 112AO

112AO

AVO - Wheel with oil-proof rubber tyre for industry, diameter 140mm

Material: Oil-proof Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with oil-proof rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings. 112AO wheel can be assembled with all medium duty castors.

Product line: Rubber tyre

EAN13:/ **EAN5:/** **Article code:**0311200140ORN



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 115 DaN
Rotation: Roller bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	140
Band width (mm)	38
Hub width (mm)	43
Hub version	Roller bearing
Wheel hole (mm)	10
Bearing seat (mm)	/
Dynamic load capacity (DaN)	115
Colour	Black
Material	Oil-proof Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/