

SERIE 112AO

112AO

AVO - Wheel with oil-proof rubber tyre for industry, diameter 150mm

Material: Oil-proof Rubber tyre **Core:** Steel **Application field:** Industry

Description:

Wheel with oil-proof rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings. 112AO wheel can be assembled with all medium duty castors.

Product line: Rubber tyre

EAN13:/ **EAN5:/** **Article code:**0311200150ORN

Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 135 DaN
Rotation: Roller bearing **Hardness scale:** Shore A **Hardness:** 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-----------------------|
| Diameter (mm) | 150 |
| Band width (mm) | 40 |
| Hub width (mm) | 43 |
| Hub version | Roller bearing |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 135 |
| Colour | Black |
| Material | Oil-proof Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| | |
|----------------------------|---|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | / |
| Ground clearance (mm) | / |
| Castor hole (mm) | / |
| Static load capacity (DaN) | / |
| Structure | / |
| Version | / |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | / |