

SERIE 46

## 54BIS

**AVO - Wheel with pneumatic rubber tyre and steel castor for industry, diameter 200mm ean 10969**

**Material:** Pneumatic Rubber tyre    **Core:** Steel    **Scope:** Industry

**Description:**

Pneumatic wheel with inner tube. Flanges in zinc-chromium plated pressed steel. Hub on roller bearings, shielded ball bearings or self oiling bushes.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Pneumatic

**EAN13:** 8018793109697    **EAN5:** 10969    **Article code:** 190540F2000RF



## Features

**Minimum temperature:** -40    **Maximum temperature:** 80    **Dynamic load capacity:** 75 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore A    **Hardness:** 80

## Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

## Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	75
Colour	Black
Material	Pneumatic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

## Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	100
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized