

SERIE 41

44A

AVO - Wheel with pneumatic rubber tyre and steel castor for industry, diameter 260mm ean 10225

Material: Pneumatic
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Pneumatic wheel tyre with inner tube and thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Pneumatic

EAN13: 8018793102254

EAN5: 10225

Article code: 19044A02600RP



Features

Minimum temperature: -40	Maximum temperature: 80	Dynamic load capacity: 150 DaN
Rotation: Roller bearing	Hardness scale: Shore A	Hardness: 80

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	260
Band width (mm)	85
Hub width (mm)	75
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Black
Material	Pneumatic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	200X160
Plate hole spacing (mm)	150X115
Plate hole size (mm)	14X26
Offset (mm)	/
Ground clearance (mm)	307
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized