

SERIE 46

54

AVO - Wheel with pneumatic rubber tyre and steel castor for industry, diameter 260mm ean 10265

Material: Pneumatic Rubber tyre

Core: Steel

Application field: Industry

Description:

Pneumatic wheel with inner tube. Flanges in zinc-chromium plated pressed steel. Hub on roller bearings, shielded ball bearings or self oiling bushes.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Pneumatic

EAN13:8018793102650

EAN5:10265

Article code:19054002600RF



Features

Minimum temperature: -40

Maximum temperature: 80

Dynamic load capacity: 150 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	260
Band width (mm)	85
Hub width (mm)	88
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Black
Material	Pneumatic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	200X160
Plate hole spacing (mm)	150X115
Plate hole size (mm)	14X26
Offset (mm)	85
Ground clearance (mm)	307
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized