

SERIE 41

44BISB

AVO - Wheel with pneumatic rubber tyre and steel castor for industry, diameter 260mm ean 10957

Material: Pneumatic
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Pneumatic wheel tyre with inner tube and thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut.

Product line: Pneumatic

EAN13:8018793109574 **EAN5:**10957 **Article code:**19044BF2600BP



Features

Minimum temperature: -40	Maximum temperature: 80	Dynamic load capacity: 150 DaN
Rotation: Plain bore	Hardness scale: Shore A	Hardness: 80

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	260
Band width (mm)	85
Hub width (mm)	75
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Black
Material	Pneumatic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	85
Ground clearance (mm)	303
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	25X55
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized