

SERIE 46

## 54BISB

**AVO - Wheel with pneumatic rubber tyre and steel castor for industry, diameter 260mm ean 10964**

**Material:** Pneumatic Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Pneumatic wheel with inner tube. Flanges in zinc-chromium plated pressed steel. Hub on roller bearings, shielded ball bearings or self oiling bushes.

**Medium duty castors:**

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

**Product line:** Pneumatic

**EAN13:** 8018793109642

**EAN5:** 10964

**Article code:** 19054BF2600BF



### Features

**Minimum temperature:** -40

**Maximum temperature:** 80

**Dynamic load capacity:** 150 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 80

### Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

### Wheel data

|                             |                       |
|-----------------------------|-----------------------|
| Diameter (mm)               | 260                   |
| Band width (mm)             | 85                    |
| Hub width (mm)              | 88                    |
| Hub version                 | Plain bore            |
| Wheel hole (mm)             | 20                    |
| Bearing seat (mm)           | /                     |
| Dynamic load capacity (DaN) | 150                   |
| Colour                      | Black                 |
| Material                    | Pneumatic Rubber tyre |
| Box pieces                  | /                     |
| Hardness scale              | Shore A               |
| Hardness                    | 80                    |

### Support data

|                            |                                           |
|----------------------------|-------------------------------------------|
| Plate size (mm)            | /                                         |
| Plate hole spacing (mm)    | /                                         |
| Plate hole size (mm)       | /                                         |
| Offset (mm)                | 85                                        |
| Ground clearance (mm)      | 303                                       |
| Castor hole (mm)           | /                                         |
| Static load capacity (DaN) | 190                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle with brake                           |
| Brake                      | Rear                                      |
| Plain axle                 | 25X55                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |