

SERIE 46

54BISB

AVO - Wheel with pneumatic rubber tyre and steel castor for industry, diameter 260mm ean 10966

Material: Pneumatic Rubber tyre

Core: Steel

Application field: Industry

Description:

Pneumatic wheel with inner tube. Flanges in zinc-chromium plated pressed steel. Hub on roller bearings, shielded ball bearings or self oiling bushes.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Pneumatic

EAN13:8018793109666

EAN5:10966

Article code:19054BF2600RF



Features

Minimum temperature: -40

Maximum temperature: 80

Dynamic load capacity: 150 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	260
Band width (mm)	85
Hub width (mm)	88
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Black
Material	Pneumatic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	85
Ground clearance (mm)	303
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Rear
Plain axle	25X55
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized