

SERIE 46

54BIS

AVO - Wheel with pneumatic rubber tyre with steelcastor for industry, diameter 400mm ean 17133

Material: / **Core:** Steel **Scope:** Industry

Description:

Pneumatic wheel with inner tube. Pneumatic wheel with inner tube. Flanges in zinc-chromium plated pressed steel. Hub on roller bearings, shielded ball bearings or self oiling bushes.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and rear brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Pneumatic

EAN13:8018793171335 **EAN5:**17133 **Article code:**190540F4000CF



Features

Minimum temperature: -40	Maximum temperature: 80	Dynamic load capacity: 200 DaN
Rotation: Ball bearing	Hardness scale: Shore A	Hardness: 80

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	400
Band width (mm)	100
Hub width (mm)	75
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Black
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized