

SERIE 46

54A

AVO - Wheel with pneumatic rubber tyre and steel castor for industry, diameter 400mm ean 17134

Material: Pneumatic Rubber tyre

Core: Steel

Application field: Industry

Description:

Pneumatic wheel with inner tube. Flanges in zinc-chromium plated pressed steel. Hub on roller bearings, shielded ball bearings or self oiling bushes.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Pneumatic

EAN13: 8018793171342

EAN5: 17134

Article code: 19054A04000CF



Features

Minimum temperature: -40

Maximum temperature: 80

Dynamic load capacity: 200 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Grid
- Off-Road
- Stoneware

Wheel data

Diameter (mm)	400
Band width (mm)	100
Hub width (mm)	75
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	200
Colour	Black
Material	Pneumatic Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	200X160
Plate hole spacing (mm)	150X115
Plate hole size (mm)	14X26
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	250
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized