

SERIE 16A-T

16A-T

AVO - Wheel with high temperature silicone rubber tyre for industry,
diameter 125mm ean 23175

Material: High temperature
silicone Rubber tyre

Core:
Aluminum

Application field:
Industry

Description:


Wheel with high-temperature silicone rubber tread 80 Shore A and aluminium wheel centre. Hub on shielded ball bearings.

Product line: High temperature

EAN13:8018793231756

EAN5:23175

Article code:14016A0126TCA



Features

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 200 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	200
Colour	Red
Material	High temperature silicone Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/