

SERIE 112A-AT

## 112A-AT

AVO - Wheel with high temperature silicone rubber tyre for industry,  
diameter 150mm

**Material:** High temperature silicone  
Rubber tyre

**Core:**  
Steel

**Application field:**  
Industry

**Description:**

High temperature silicone rubber tyre wheel 80 Shore A with flanges in zinc-chromium plated pressed steel. Hub on shielded ball bearings.

**Product line:** High temperature

**EAN13:/**    **EAN5:/**    **Article code:**03112A0150TCR



### Features

**Minimum temperature:** -20

**Maximum temperature:** 120

**Dynamic load capacity:** 135 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 80

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

|                             |                                       |
|-----------------------------|---------------------------------------|
| Diameter (mm)               | 150                                   |
| Band width (mm)             | 40                                    |
| Hub width (mm)              | 43                                    |
| Hub version                 | Ball bearing                          |
| Wheel hole (mm)             | 10                                    |
| Bearing seat (mm)           | /                                     |
| Dynamic load capacity (DaN) | 135                                   |
| Colour                      | Red                                   |
| Material                    | High temperature silicone Rubber tyre |
| Box pieces                  | /                                     |
| Hardness scale              | Shore A                               |
| Hardness                    | 80                                    |

### Support data

|                            |   |
|----------------------------|---|
| Plate size (mm)            | / |
| Plate hole spacing (mm)    | / |
| Plate hole size (mm)       | / |
| Offset (mm)                | / |
| Ground clearance (mm)      | / |
| Castor hole (mm)           | / |
| Static load capacity (DaN) | / |
| Structure                  | / |
| Version                    | / |
| Brake                      | / |
| Plain axle                 | / |
| Stem type                  | / |
| Finishing                  | / |