

SERIE 112A-AT

80BIS-AT

AVO - Wheels with rubber siliconica alta temperatura with castor steel for industry, diameter 100mm ean 27910

Material: / **Core:** Steel **Scope:** Industry

Description:

High temperature rubber tyre wheel 80 Shore A with flanges in zinc-chromium plated pressed steel. Hub on shielded ball bearings. Wheel 112A-AT can be assembled with medium duty castors (ø80-250 mm.)

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: High temperature

EAN13:8018793279109 **EAN5:**27910 **Article code:**01080F0100TCR

Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 70 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	34
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	70
Colour	Red
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	9X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	90
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized