

SERIE 112A-AT

103-AT

AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 125mm ean 20622

Material: High temperature silicone
Rubber tyre

Core:
Steel

Application field:
Industry

Description:

High temperature silicone rubber tyre wheel 80 Shore A with flanges in zinc-chromium plated pressed steel. Hub on shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut.

Product line: High temperature

EAN13:8018793206228

EAN5:20622

Article code:03103S0125TCR



Features

Minimum temperature: -20

Maximum temperature: 120

Dynamic load capacity: 100 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	38
Hub width (mm)	46
Hub version	Ball bearing
Wheel hole (mm)	10
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Red
Material	High temperature silicone Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized