

SERIE 16A-T

36A-T

AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 125mm ean 27667

Material: High temperature silicone Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with high-temperature silicone rubber tread 80 Shore A and aluminium wheel centre. Hub on shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: High temperature

EAN13:8018793276672 **EAN5:**27667 **Article code:**14036A0125TCA



Features

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 170 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	40
Hub width (mm)	50
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	32X9
Dynamic load capacity (DaN)	170
Colour	Red
Material	High temperature silicone Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized