

SERIE 16A-T

36-T

AVO - Wheel with high temperature silicone rubber tyre and steel castor for industry, diameter 150mm ean 25543

Material: High temperature silicone Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with high-temperature silicone rubber tread 80 Shore A and aluminium wheel centre. Hub on shielded ball bearings.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut.

Product line: High temperature

EAN13:8018793255431 **EAN5:**25543 **Article code:**1403600150TCA



Features

Minimum temperature: -40

Maximum temperature: 280

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Red
Material	High temperature silicone Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	185
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized